



## CP550SLGTAA Standby Series UPS

Offers energy savings, battery backup and surge protection.

The CyberPower Federal Trade Agreements Act (TAA) compliant Standby CP550SLGTAA uninterruptible power supply (UPS) safeguards a home office PC and other electronics (monitors, printers, scanners, speakers, fax machines, CD/DVD players and iPods) from surges, spikes, sags, brownouts and other power abnormalities. Its composite integrated circuitry offers advanced lightning protection. Patented GreenPower UPS™ advanced circuitry reduces UPS energy costs by up to 75% compared to competitive models.

This UPS system is ENERGY STAR® qualified with patented GreenPower UPS™ Bypass circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship, further protection is offered by a \$100,000 Connected Equipment Guarantee.

### Typical Applications

- Desktop Computers
- Home Networking/VoIP
- Personal Electronics

### Features

- 550VA / 330W
- Standby Topology
- GreenPower UPS™
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Compact Form Factor
- 8 Outlets / USB Port / RJ11 Protection
- EMI/RFI Filters
- PowerPanel® Personal Edition
- 3-Year Warranty

# CP550SLGTAA Standby Series UPS

Offers energy savings, battery backup and surge protection.

GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	96Vac - 140Vac
Frequency	47Hz - 63Hz
Circuit Breaker	10 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45 Degree Offset Right
Cord Length	5'
OUTPUT	
VA	550
Watts	330
On Battery Voltage	120Vac ± 5%
On Battery Frequency	50/60Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlet Type	NEMA 5-15R
Outlets - Total	8
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms
BATTERY	
Runtime at Half Load (min)	8
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12V/5.5AH
Battery Quantity	1
User Replaceable	No
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	890 Joules
Phone Protection RJ11	1-In, 2-Out
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS	
HID Compliant USB Port	Yes
Serial Port	No
Cable Management	USB Cable
LED Indicators	Power On, Wiring Fault
Audible Alarms	On Battery, Low Battery, Overload
Software	PowerPanel® Personal Edition
PHYSICAL	
Form Factor	Compact
Keyhole Mounting Slots	Yes
Dimensions (WxHxD) (in.)	9.75 x 6 x 3
Weight (lbs.)	6.4
ENVIRONMENTAL	
Operating Temperature	32 °F to 95 °F / 0 °C to 35 °C
Operating Humidity	0% - 90% non-condensing
CERTIFICATIONS	
Safety	UL1778, cUL 107.3, FCC DOC Class B
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$100,000

