

The logo for ThinkVision U.S. features the word "ThinkVision" in a bold, black, sans-serif font, with a red dot above the "i". To the right of "ThinkVision" is a blue rectangular box with a white border, containing the letters "U.S." in a white, sans-serif font.

## Product Specifications Reference

[illegible]

Version 467, January 2015

**ThinkVision® Monitors**

**lenovo**® FOR  
THOSE  
WHO DO.

Visit [www.lenovo.com/psref](http://www.lenovo.com/psref) for the latest version

# Contents

---

Summary of Changes .....	1
Lenovo ThinkVision E1922 Wide.....	2
Lenovo ThinkVision E2223s Wide.....	3
Lenovo ThinkVision E2323 Wide.....	4
Lenovo ThinkVision LT1421 Wide Mobile Monitor .....	5
Lenovo ThinkVision LT1423p Mobile Touch Monitor (Wired) .....	6
Lenovo ThinkVision LT1423p Mobile Touch Monitor (Wireless) .....	7
Lenovo ThinkVision LT1713p .....	8
Lenovo ThinkVision LT1913p Square .....	9
Lenovo ThinkVision LT1952p Wide .....	10
Lenovo ThinkVision LT1953 Wide .....	11
Lenovo ThinkVision LT2013p Wide .....	12
Lenovo ThinkVision LT2013s Wide .....	13
Lenovo ThinkVision LT2024 Wide .....	14
Lenovo ThinkVision LT2223p Wide .....	15
Lenovo ThinkVision LT2223z Wide .....	16
Lenovo ThinkVision LT2252p Wide .....	17
Lenovo ThinkVision LT2323p Wide .....	18
Lenovo ThinkVision LT2323z Wide .....	19
Lenovo ThinkVision LT2423 Wide .....	20
Lenovo ThinkVision LT2452p Wide .....	21
Lenovo ThinkVision Pro2820 Wide .....	22
Lenovo ThinkVision Pro2840m Wide .....	23
Lenovo ThinkVision 28 .....	<a href="#">24</a>
Lenovo ThinkVision T2014 Wide.....	25
Withdrawn Product Books.....	26
Legal Information and Trademarks.....	27

# Summary of Changes

---

This section describes the technical changes made in this edition.

This edition might also include minor corrections and editorial changes which are not identified.

## January 28, 2015 - Version 467

### Additions in this update

#### ► New product(s)

Lenovo ThinkVision T2014 new product announced

#### ► Others


None

### Changes in this update

► None

### Withdrawals in this update




► None

<div>Name Case color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD)  Power supply  Weight Limited warranty<sup>4</sup> Available date</div> <div>E1922 Wide Flat Panel Monitor Business black 60B8AAR6US TFT-LCD, twisted nematic (TN), White LED backlight 18.5" (470mm) diagonal 16.1" x 9.1" / 409.8mm x 230.4mm 1366x768 16:9 .300mm 85 dpi 250 nits or cd/m<sup>2</sup> (typical) 1000:1 (typical) 5ms (typical) 72% 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt adjustable stand Sides: 0.73" (18.5mm) 13.44" H x 17.65" W x 6.58" D; 341.5mm H x 448.4mm W x 167.2mm D 13.7 watts typical, 17 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 6.03 lb; 2.74 kg 3 year (includes backlight) March 2014</div>		<div>Features</div> <ul style="list-style-type: none"><li>• Widescreen 18.5-inch monitor</li><li>• Supports HD 1366x768 resolution</li><li>• Supports VESA mount (100mm)</li><li>• Mercury free panel and arsenic free glass</li><li>• Kensington lock slot ready for enhanced security</li><li>• Support Lenovo Tiny PC via VESA mount</li><li>• Microsoft® Windows® 7 certified</li><li>• Microsoft Windows 8 / Windows 8.1 certified</li></ul>
<div>VESA-compliant<sup>2</sup> Power management Ergonomics Emission standards Environmental</div> <div>VESA DPMS-compliant ENERGY STAR® 6.0 ISO 9241-307 FCC Class B TCO (TCO Displays 6.0), WEEE, RoHS, EPEAT™ Gold rating</div>		<div></div> <div>ThinkVision E1922 Wide Monitor</div>
<div>Preset resolutions</div> <div>VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768</div> <div>Presets / user settings</div> <div>Standard presets: 15 user settings: 16</div>		
<div>Viewing adjustments Rotating screen On screen display Control features Multiple input Monitor connectors Signal cables Mounting features Security</div> <div>Tilt: 20° backward, -5° forward None On screen display with digital user controls (8 languages) Direct access (control buttons on front) for automatic image setup and adjustment for brightness None VGA 15-pin D-shell, analog, blue detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>		
<div>Ship group</div> <div>Monitor with stand, 1.8 meter analog signal cable, 1.8 meter black power cord</div>		
<div>Limited Warranty</div> <div>See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a></div>		
<div>Accessories</div> <div><div>Kensington MicroSaver Cable Lock73P2582</div><div>Kensington Twin Head Cable Lock45K1620</div></div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>		

<div><div>Name</div><div>Case color</div><div>Type-model</div><div>Panel</div><div>Viewable image size</div><div>Max view area (W x H)</div><div>Native resolution</div><div>Aspect ratio</div><div>Pixel pitch (mm)</div><div>Dot/Pixel per Inch</div><div>Brightness</div><div>Contrast ratio</div><div>Pixel response time</div><div>Color gamut</div><div>Viewing angle at 10:1 CR</div><div>Stand</div><div>Bezel width</div><div>Dimensions (HxWxD)</div><div>Power supply</div><div>Weight</div><div>Limited warranty<sup>4</sup></div><div>Available date</div></div> <div><div>E2223s Wide Flat Panel Monitor</div><div>Business black</div><div>60AFHAR1US</div><div>TFT-LCD, twisted nematic (TN), White LED backlight</div><div>21.5" (546mm) diagonal</div><div>18.7" x 10.5" / 476.1mm x 267.8mm</div><div>1920x1080</div><div>16:9</div><div>.248mm</div><div>102 dpi</div><div>200 nits or cd/m² (typical)</div><div>600:1 (typical)</div><div>5ms (typical)</div><div>72%</div><div>90° (+/- 45°) horizontal, 50° (+/- 25°) vertical</div><div>Tilt adjustable stand</div><div>Sides: 0.72" (18.3mm)</div><div>14.94" H x 20.60" W x 6.58" D;</div><div>379.4mm H x 514.5mm W x 167.2mm D</div><div>19 watts typical, 22 watts maximum,</div><div>&lt;0.5 watts standby/suspend, universal,</div><div>integrated (no external brick-like power supply)</div><div>7.52 lb; 3.4 kg</div><div>3 year (includes backlight)</div><div>March 2014</div></div>		<div><div>Features</div><div><div>• Widescreen 21.5-inch monitor</div><div>• Supports FHD 1920x1080 resolution</div><div>• Supports VESA mount (100mm)</div><div>• Kensington lock slot ready for enhanced security</div><div>• Microsoft® Windows® 7 certified</div><div>• Microsoft Windows 8 certified</div></div></div>
<div><div>Power management</div><div>Ergonomics</div><div>Emission standards</div><div>Environmental</div></div> <div><div>ENERGY STAR® 6.0</div><div>ISO 9241-307</div><div>FCC Class B</div><div>WEEE, RoHS, EPEAT™ SILVER rating</div></div>	<div><div><div>ThinkVision E2223s</div><div><div></div></div><div>lenovo</div></div><div></div><div></div></div> <div>ThinkVision E2223s Wide Monitor</div>	
<div><div>Preset resolutions</div></div> <div><div>VGA:</div><div>SVGA:</div><div>XGA:</div><div>SXGA:</div><div>WXGA:</div><div>WXGA+:</div><div>WSXGA+:</div><div>Full HD:</div></div> <div><div>640x350, 640x480, 720x400</div><div>800x600, 832x624</div><div>1024x768, 1152x864</div><div>1280x1024</div><div>1366x768</div><div>1440x900, 1600x900</div><div>1680x1050</div><div>1920x1080</div></div>		
<div><div>Presets / user settings</div></div> <div><div>Standard presets: 26</div><div>user settings: 26</div></div>		
<div><div>Viewing adjustments</div><div>Rotating screen</div><div>On screen display</div><div>Control features</div><div>Multiple input</div><div>Monitor connectors</div></div> <div><div>Tilt: 22° backward, -5° forward</div><div>None</div><div>On screen display with digital user controls (8 languages)</div><div>Direct access (buttons on front) for automatic image setup, dual input and brightness</div><div>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</div><div>(1) VGA 15-pin D-shell, analog, blue</div><div>(2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></div></div>		
<div><div>Signal cables</div><div>Mounting features</div><div>Security</div></div> <div><div>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div><div>(2) detachable, DVI-D at each end, digital, 1.8 meter</div><div>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div><div>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div></div>		
<div><div>Ship group</div></div> <div><div>Monitor with stand, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</div></div>		
<div><div>Limited Warranty</div><div>See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a></div></div>	<div><div>Accessories</div><div><div><div>Kensington MicroSaver Cable Lock</div><div>73P2582</div></div><div><div>Kensington Twin Head Cable Lock</div><div>45K1620</div></div></div><div><div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div><div><div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div></div></div></div>	


A black Lenovo ThinkVision E2323 monitor is shown from a front-facing perspective. The monitor has a wide, flat bezel and is mounted on a black, curved stand. The screen is dark and displays the text "ThinkVision E2323" in the top left corner. The Lenovo logo is visible on the bottom bezel. On the right side of the bottom bezel, there are several small, circular ports or buttons. The background is a plain, light gray.




<p>Name <b>LT1421 Wide Mobile Monitor</b>  Case color <b>Raven black</b>  Type-model <b>1452-DS6 (with Protective Screen Cover)</b>  Panel <b>TFT-LCD, twisted nematic (TN), White LED backlight</b>  Viewable image size <b>14.0" (355.6mm) diagonal</b>  Max view area (W x H) <b>12.2" x 6.9" (310.8mm x 175.3mm)</b>  Optimum resolution <b>1366x768</b>  Aspect ratio <b>16:9</b>  Pixel pitch (mm) <b>.227mm</b>  Dot/Pixel per Inch <b>112 dpi</b>  Brightness <b>200 nits or cd/m<sup>2</sup> (typical)</b>  Contrast ratio <b>400:1 (typical)</b>  Pixel response time <b>8ms (typical)</b>  Color gamut <b>45%</b>  Viewing angle at 10:1 CR <b>90° (+/- 45°) horizontal, 50° (+/- 25°) vertical</b>  Stand <b>Tilt adjustable stand</b>  Bezel width <b>Sides: 0.476" (12.1mm)</b>  Dimensions (HxWxD) <b>8.58" H x 13.19" W x 0.37-0.85" D;  217.9mm H x 335mm W x 9.3-21.5mm D</b>  Power supply <b>4.2 watts typical, 5 watts maximum,  &lt;0.1 watts standby/suspend, universal,  USB 2.0 cable (no external brick-like power supply)</b>  Weight <b>monitor only: 1.91 lb; 0.87 kg;  with Protective Screen Cover: 2.31 lb; 1.05 kg</b>  Limited warranty<sup>4</sup> <b>3 year (includes backlight)</b>  Available date <b>September 2011</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 14-inch mobile monitor designed for ThinkPad</li> <li>• Light and Slim</li> <li>• Super low power (&lt;5 watts)</li> <li>• Supports 1366x768 resolution</li> <li>• Ergonomic stand tilts, provides a 12° - 40° backward tilt adjustment for comfortable viewing</li> <li>• Detachable USB cable for power and signal</li> <li>• Microsoft® Windows® 7 certified</li> </ul>  <p><b>ThinkVision LT1421 Wide Mobile Monitor</b></p>				
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, VESA DPMS-compliant</b>  Power management <b>ENERGY STAR<sup>®</sup> 5.1</b>  Emission standards <b>FCC Class B</b>  Environmental <b>WEEE, RoHS</b>  Preset resolutions <b>Display mode and resolution auto setup</b></p>	 <p><b>ThinkVision LT1421 Wide Mobile Monitor with ThinkPad Edge E420s</b></p>				
<p>Protective Screen Cover <b>Polycarbonate Snap-On Cover protects the LCD Screen while not in use</b></p>	 <p><b>ThinkVision LT1421 with Protective Screen Cover</b></p>				
<p>Viewing adjustments <b>Tilt: 12° - 40° backward</b>  Screen control <b>Brightness (16 levels)</b>  Input <b>USB input</b>  Monitor connectors <b>USB 2.0</b>  Signal cables <b>detachable, USB Y-Type cable, 1.8 meter</b>  Mounting features <b>None</b>  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>					
<p>Ship group</p>	<p>Monitor, attached tile stand that cannot be removed, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter USB Y-Type cable, Protective Screen Cover</p>				
<p><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>3 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>International Warranty Service<sup>5</sup></b></li> <li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>Service upgrade options<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> </li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p><b>Accessories</b></p> <table> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				


<p> <b>Name</b> LT1423p Mobile Touch Monitor w/pen  <b>Case color</b> Raven black  <b>Type-model</b> 60A3UAR2US (with Digitizer pen)  <b>Panel</b> TFT-LCD, AH-IPS, White LED backlight  <b>Viewable image size</b> 13.3" (337.8mm) diagonal  <b>Max view area (W x H)</b> 11.57" x 6.50" (293.8mm x 165.2mm)  <b>Optimum resolution</b> 1600x900  <b>Aspect ratio</b> 16:9  <b>Pixel pitch (mm)</b> .184mm  <b>Dot/Pixel per Inch</b> 138 dpi  <b>Brightness</b> 200 nits or cd/m<sup>2</sup> (typical)  <b>Contrast ratio</b> 500:1 (typical)  <b>Pixel response time</b> 35ms (typical)  <b>Color gamut</b> 45%  <b>Viewing angle at 10:1 CR</b> 150° (+/- 75°) horizontal, 150° (+/- 75°) vertical  <b>Stand</b> Build in typing stand  <b>Bezel width</b> Sides: 1.04" (26.5mm);                      top: 1.16" (29.5mm);                      bottom: 1.16" (29.5mm)  <b>Dimensions (HxWxD)</b> 8.87" H x 13.70" W x 0.26-0.50" D;                      225.4mm H x 348.0mm W x 6.7-12.7mm D  <b>Power supply</b> 6.0 watts typical, 7.0 watts maximum,                      &lt;1.5 watts standby/suspend, universal,                      USB 3.0 cable (no external brick-like power supply)  <b>Weight</b> 1.87 lb; 0.85 kg  <b>Limited warranty<sup>4</sup></b> 3 year (includes backlight)  <b>Available date</b> September 2013                 </p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 13.3-inch mobile Touch monitor</li> <li>• Supports 10-point touch</li> <li>• Supports ThinkPad Digitizer pen</li> <li>• Supports 1600x900 resolution</li> <li>• Detachable USB cable for power and signal</li> <li>• Arsenic/Mercury free</li> <li>• Microsoft® Windows® 7 certified</li> <li>• Microsoft® Windows® 8 certified</li> </ul> 				
<p> <b>VESA-compliant<sup>2</sup></b> None  <b>Power management</b> None  <b>Emission standards</b> FCC Class B  <b>Environmental</b> RoHS  <b>Preset resolutions</b> SVGA: 800x600                      XGA: 1024x768                      SXGA: 1280x1024                      WXGA: 1280x720, 1280x800, 1366x768                      WXGA+: 1440x900, 1600x900  <b>Presets / user settings</b> 7                 </p>					
<p> <b>Build in typing Stand</b> Yes  <b>Touch Screen</b> 10-point touch  <b>Digitizer Pen</b> ThinkPad Digitizer pen  <b>Input</b> USB input  <b>Monitor connectors</b> USB 3.0  <b>Signal cables</b> detachable, USB to mini-USB cable, 100cm                      detachable, USB Y-Type cable, 45cm  <b>Mounting features</b> None  <b>Security</b> Security keyhole for attachment of optional cable lock                      (Kensington® lock-compatible)  <b>Protective glass layer</b> Gorilla glass  <b>Simple Cover Stand</b> Yes  <b>Digital Control key</b> 3 digital control keys  <b>Battery</b> None                 </p>	 <p><b>ThinkVision LT1423p</b></p>				
<p><b>Ship group</b></p>	<p>Monitor, build in typing stand that cannot be removed, Setup poster, Safety and Warranty Information, 100cm USB to mini-USB cable, 45cm USB Y-Type cable, Simple Cover Stand, ThinkPad Digitizer pen</p>				
<p> <b>Limited Warranty</b>                      See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a> </p>	<p><b>Accessories</b></p> <table> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				



<p> <b>Name</b> LT1423p Mobile Touch Monitor w/pen (Wireless)  <b>Case color</b> Raven black  <b>Type-model</b> 60ACUAR2US (with Digitizer pen)  <b>Panel</b> TFT-LCD, AH-IPS, White LED backlight  <b>Viewable image size</b> 13.3" (337.8mm) diagonal  <b>Max view area (W x H)</b> 11.57" x 6.50" (293.8mm x 165.2mm)  <b>Optimum resolution</b> 1600x900  <b>Aspect ratio</b> 16:9  <b>Pixel pitch (mm)</b> .184mm  <b>Dot/Pixel per Inch</b> 138 dpi  <b>Brightness</b> 200 nits or cd/m<sup>2</sup> (typical)  <b>Contrast ratio</b> 500:1 (typical)  <b>Pixel response time</b> 35ms (typical)  <b>Color gamut</b> 45%  <b>Viewing angle at 10:1 CR</b> 150° (+/- 75°) horizontal, 150° (+/- 75°) vertical  <b>Stand</b> Build in typing stand  <b>Bezel width</b> Sides: 1.04" (26.5mm);                      top: 1.16" (29.5mm);                      bottom: 1.16" (29.5mm)  <b>Dimensions (HxWxD)</b> 8.87" H x 13.70" W x 0.50" D;                      225.4mm H x 348.0mm W x 12.7mm D  <b>Power supply</b> 13.0 watts typical, 16.0 watts maximum,                      &lt;0.5 watts standby/suspend, universal,                      USB 3.0 cable (no external brick-like power supply)  <b>Weight</b> 2.86 lb; 1.30 kg  <b>Limited warranty<sup>4</sup></b> 1 year (includes backlight)  <b>Available date</b> October 2013                 </p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 13.3-inch mobile Touch monitor (Wireless)</li> <li>• 8m wireless range and up to 4 hours battery</li> <li>• Supports 10-point touch</li> <li>• Supports ThinkPad Digitizer pen</li> <li>• Supports 1600x900 resolution</li> <li>• Arsenic/Mercury free</li> <li>• Microsoft® Windows® 7 certified</li> <li>• Microsoft® Windows® 8 certified</li> </ul>
<p> <b>VESA-compliant<sup>2</sup></b> None  <b>Power management</b> None  <b>Emission standards</b> FCC Class B  <b>Environmental</b> RoHS  <b>Preset resolutions</b> SVGA: 800x600                      XGA: 1024x768                      WXGA: 1280x720, 1280x800, 1366x768                      WXGA+: 1440x900, 1600x900  <b>Presets / user settings</b> 7                 </p>	 <p><b>ThinkVision LT1423p (Wireless)</b></p>
<p> <b>Build in typing Stand</b> Yes  <b>Touch Screen</b> 10-point touch  <b>Digitizer Pen</b> ThinkPad Digitizer pen  <b>Input</b> WiFi 802.11 a/b/g/n and USB input  <b>Monitor connectors</b> USB 3.0  <b>Signal cables</b> detachable, USB to mini-USB cable, 100cm                      detachable, USB Y-Type cable, 45cm  <b>Mounting features</b> None  <b>Security</b> Security keyhole for attachment of optional cable lock                      (Kensington® lock-compatible)  <b>Protective glass layer</b> Gorilla glass  <b>Simple Cover Stand</b> Yes  <b>Digital Control key</b> 4 digital control keys  <b>Battery</b> 8120 mAh                 </p>	<p> <b>Ship group</b> Monitor, build in typing stand that cannot be removed, Setup poster, Safety and Warranty Information, 100cm USB to mini-USB cable, 45cm USB Y-Type cable, USB WiFi dongle, Simple Cover Stand, ThinkPad Digitizer pen                 </p>
<p> <b>Limited Warranty</b>                      See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a> </p>	<p> <b>Accessories</b>                      Kensington MicroSaver Cable Lock 73P2582                      Kensington Twin Head Cable Lock 45K1620                        See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                        See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a> </p>

Name	LT1713p Square Flat Panel Monitor	<b>Features</b> <ul style="list-style-type: none"><li>• 17-inch Square LCD monitor</li><li>• Supports SXGA 1280x1024 resolution</li><li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li><li>• Arsenic free glass</li><li>• Supports Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket</li><li>• Microsoft® Windows® 7 certified</li><li>• Microsoft Windows 8 certified</li><li>• Microsoft Windows 8.1 certified</li></ul>						
Case color	Business black							
Type-model	60B3HAR2US	 <b>ThinkVision LT1713p Monitor</b>						
Panel	TFT-LCD, twisted nematic (TN), LED backlight							
Viewable image size	17.0" (432mm) diagonal							
Max view area (W x H)	13.3" x 10.6" (337.9mm x 270.3mm)							
Optimum resolution	1280x1024							
Aspect ratio	5:4							
Pixel pitch (mm)	0.264mm							
Dot/Pixel per Inch	96 dpi							
Brightness	250 nits or cd/m² (typical)							
Contrast ratio	1000:1 (typical)							
Pixel response time	5ms (typical)							
Color gamut	72%							
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical							
Stand	Tilt height adjustable stand							
Bezel width	Sides: 0.60" (15.3mm); top: 0.73" (18.4mm); bottom: 1.10" (28.1mm)							
Dimensions	16.0" H x 14.6" W x 6.5" D;							
(HxWxD, including stand)	405.7mm H x 370.0mm W x 165.2mm D							
Power supply	13.0 watts typical, 16.0 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)							
Weight	7.90 lb; 3.60kg							
Limited warranty <sup>4</sup>	3 year (includes backlight)							
Available date	January 2014							
VESA-compliant <sup>2</sup>	VESA DDC2B/CI, VESA DPMS-compliant							
Power management	ENERGY STAR® 6.0							
Ergonomics	ISO 9241-307							
Emission standards	FCC Class B							
Environmental	TCO Displays 6.0, TCO Certified Edge 1.2, WEEE, RoHS, EPEAT™ Gold rating							
Preset resolutions	VGA: 640x350, 640x480, 640x500, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864, SXGA: 1280x1024							
Presets / user settings	Standard presets: 17; user settings: 22							
Viewing adjustments	Tilt: 22° back, -3° forward; lift: 4.3" (110mm)							
Rotating screen	None							
On screen display	On screen display with digital user controls (8 languages)							
Control features	Direct access (buttons on front) for automatic image setup							
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)							
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>							
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter							
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)							
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)							
Ship group	Monitor and stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord							
<b>Limited Warranty</b> See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a>		<b>Accessories</b> <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr></table> See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>  See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington MicroSaver Cable Lock	73P2582							
Kensington Twin Head Cable Lock	45K1620							
Lenovo Easy Reach Monitor Stand	55Y9258							

Name	LT1913p Square Flat Panel Monitor	<b>Features</b> <ul style="list-style-type: none"><li>• 19-inch Square IPS LED backlit panel</li><li>• Supports 1280x1024 resolution</li><li>• Support Lenovo Tiny PC via optional Lenovo bracket</li><li>• Mercury and arsenic free glass</li><li>• Low Halogen</li><li>• Recycled content in plastic material</li><li>• Microsoft® Windows® 7 certified</li><li>• Microsoft Windows 8 certified</li></ul>
Case color	Business black	
Type-model	60AAHAR1US	
Panel	TFT-LCD, In-Plane Switching (IPS), White LED backlight	
Viewable image size	19" (480.0mm) diagonal	
Max view area (W x H)	14.76" x 11.80" (374.8mm x 299.8mm)	
Optimum resolution	1280x1024	
Max pixel rate	205MHz (VGA), 165MHz (DVI)	
Aspect ratio	5:4	
Pixel pitch (mm)	0.0976 (H) x 0.2928 (V) mm	
Dot/Pixel per Inch	86.8 dpi	
Brightness	250 nits or cd/m² (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	7ms (typical)	
Color gamut	72%	
Viewing angle at 10:1 CR	178° horizontal, 178° vertical	
Stand	Tilt, swivel, pivot, and height adjustable stand	
Bezel width	Sides: 0.69" (17.4mm); top: 0.69" (17.4mm); bottom: 0.69" (17.4mm)	
Dimensions (HxWxD)	14.89" H x 16.18" W x 8.74" D; 378.3mm H x 411.0mm W x 221.9mm D	
Power supply	24 watts typical, 27 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)	
Weight	10.03 lb; 4.55kg	
Limited warranty <sup>4</sup>	3 year (includes backlight)	
Available date	August 2013	
VESA-compliant <sup>2</sup>	VESA DDC2B/CI, EDID 1.3	
Power management	ENERGY STAR® 6.0	
Ergonomics	ISO 9241-307	
Emission standards	FCC Class B	
Environmental	TCO Displays 6.0, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold	
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 823x624 XGA: 1024x768, 1152x864, 1152x900 SXGA: 1280x1024	
Presets / user settings	Standard presets: 20; user settings: 20	
Viewing adjustments	Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +/- 45°	
Rotating screen	Screen pivots 90 degrees from landscape to portrait	
On screen display	On screen display with digital user controls (8 languages)	
Control features	Direct access (buttons on front) for automatic image setup, input switch, and brightness	
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)	
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>	
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter	
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group	Monitor, attached stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord	





ThinkVision LT1913p Square Monitor

<b>Limited Warranty</b>  See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a>	<b>Accessories</b> <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr></table> See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>  See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington MicroSaver Cable Lock	73P2582								
Kensington Twin Head Cable Lock	45K1620								
Lenovo Security Cable Lock	57Y4303								
Lenovo Easy Reach Monitor Stand	55Y9258								


<table><tr><td>Name</td><td><b>LT1952p Wide Flat Panel Monitor</b></td></tr><tr><td>Case color</td><td><b>Business black</b></td></tr><tr><td>Type-model</td><td><b>2448-MB6</b></td></tr><tr><td>Panel</td><td>TFT-LCD, twisted nematic (TN), White LED backlight</td></tr><tr><td>Viewable image size</td><td><b>19" (482.6mm)</b> diagonal</td></tr><tr><td>Max view area (W x H)</td><td>16.07" x 10.05" (408.2mm x 255.2mm)</td></tr><tr><td>Optimum resolution</td><td><b>1440x900</b></td></tr><tr><td>Max pixel rate</td><td>137MHz</td></tr><tr><td>Aspect ratio</td><td>16:10</td></tr><tr><td>Pixel pitch (mm)</td><td>0.2835mm</td></tr><tr><td>Dot/Pixel per Inch</td><td>89.4 dpi</td></tr><tr><td>Brightness</td><td>250 nits or cd/m<sup>2</sup> (typical)</td></tr><tr><td>Contrast ratio</td><td>1000:1 (typical)</td></tr><tr><td>Pixel response time</td><td>5ms (typical)</td></tr><tr><td>Color gamut</td><td>72%</td></tr><tr><td>Anti-reflective</td><td>Anti-reflective, anti-glare</td></tr><tr><td>Viewing angle at 10:1 CR</td><td>170° horizontal, 160° vertical</td></tr><tr><td>Stand</td><td>Tilt, swivel, and height adjustable stand</td></tr><tr><td>Bezel width</td><td><i>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</i></td></tr><tr><td>Dimensions (HxWxD)</td><td>15.66-19.99" H x 17.36" W x 6.74" D; 397.7-507.7mm H x 440.9mm W x 171.3mm D</td></tr><tr><td>Power supply</td><td>13 watts typical, 17 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</td></tr><tr><td>Weight</td><td>9.49 lb; 4.30kg</td></tr><tr><td>Limited warranty<sup>4</sup></td><td><b>3 year</b> (includes backlight)</td></tr><tr><td>Available date</td><td>September 2011</td></tr><tr><td>VESA-compliant<sup>2</sup></td><td>VESA DDC2B/CI</td></tr><tr><td>Power management</td><td>ENERGY STAR<sup>®</sup> 5.1</td></tr><tr><td>Ergonomics</td><td>ISO 9241-307</td></tr><tr><td>Emission standards</td><td>MPR-2, FCC Class B</td></tr><tr><td>Environmental</td><td>TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b>, ULE Gold</td></tr><tr><td>Preset resolutions</td><td>VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1366x768 WXGA+: 1440x900</td></tr><tr><td>Presets / user settings</td><td>Standard presets: 22; user settings: 22</td></tr><tr><td>Viewing adjustments</td><td><i>Tilt: 20° back, -3° forward; lift: 4.3" (110mm); swivel: +/-180°; detachable stand</i></td></tr><tr><td>Rotating screen</td><td>None</td></tr><tr><td>On screen display</td><td>On screen display with digital user controls (8 languages)</td></tr><tr><td>Control features</td><td>Direct access (buttons on front) for automatic image setup, input switch, and brightness</td></tr><tr><td>Multiple input</td><td>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</td></tr><tr><td>Monitor connectors</td><td>(1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></td></tr><tr><td>Signal cables</td><td>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</td></tr><tr><td>Mounting features</td><td>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</td></tr><tr><td>Security</td><td>Security keyhole for attachment of optional cable lock (Kensington<sup>®</sup> lock-compatible)</td></tr><tr><td>Ship group</td><td>Monitor, attached stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</td></tr></table>		Name	<b>LT1952p Wide Flat Panel Monitor</b>	Case color	<b>Business black</b>	Type-model	<b>2448-MB6</b>	Panel	TFT-LCD, twisted nematic (TN), White LED backlight	Viewable image size	<b>19" (482.6mm)</b> diagonal	Max view area (W x H)	16.07" x 10.05" (408.2mm x 255.2mm)	Optimum resolution	<b>1440x900</b>	Max pixel rate	137MHz	Aspect ratio	16:10	Pixel pitch (mm)	0.2835mm	Dot/Pixel per Inch	89.4 dpi	Brightness	250 nits or cd/m <sup>2</sup> (typical)	Contrast ratio	1000:1 (typical)	Pixel response time	5ms (typical)	Color gamut	72%	Anti-reflective	Anti-reflective, anti-glare	Viewing angle at 10:1 CR	170° horizontal, 160° vertical	Stand	Tilt, swivel, and height adjustable stand	Bezel width	<i>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</i>	Dimensions (HxWxD)	15.66-19.99" H x 17.36" W x 6.74" D; 397.7-507.7mm H x 440.9mm W x 171.3mm D	Power supply	13 watts typical, 17 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)	Weight	9.49 lb; 4.30kg	Limited warranty <sup>4</sup>	<b>3 year</b> (includes backlight)	Available date	September 2011	VESA-compliant <sup>2</sup>	VESA DDC2B/CI	Power management	ENERGY STAR <sup>®</sup> 5.1	Ergonomics	ISO 9241-307	Emission standards	MPR-2, FCC Class B	Environmental	TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b> , ULE Gold	Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1366x768 WXGA+: 1440x900	Presets / user settings	Standard presets: 22; user settings: 22	Viewing adjustments	<i>Tilt: 20° back, -3° forward; lift: 4.3" (110mm); swivel: +/-180°; detachable stand</i>	Rotating screen	None	On screen display	On screen display with digital user controls (8 languages)	Control features	Direct access (buttons on front) for automatic image setup, input switch, and brightness	Multiple input	Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)	Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>	Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)	Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI <sup>®</sup> (100mm mount)	Security	Security keyhole for attachment of optional cable lock (Kensington <sup>®</sup> lock-compatible)	Ship group	Monitor, attached stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord	<table><tr><th colspan="2">Features</th></tr><tr><td colspan="2"><ul style="list-style-type: none"><li>• Widescreen 19-inch monitor</li><li>• Supports 1440x900 resolution</li><li>• Ergonomic stand tilts, swivel, and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Cable Management for better user experience</li><li>• Mercury and arsenic free glass</li><li>• Recycled content in plastic material</li><li>• Privacy Filter Slot</li><li>• Microsoft<sup>®</sup> Windows<sup>®</sup> 7 certified</li></ul></td></tr><tr><td colspan="2"></td></tr><tr><td colspan="2"><b>ThinkVision LT1952p Wide Monitor</b></td></tr></table>	Features		<ul style="list-style-type: none"><li>• Widescreen 19-inch monitor</li><li>• Supports 1440x900 resolution</li><li>• Ergonomic stand tilts, swivel, and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Cable Management for better user experience</li><li>• Mercury and arsenic free glass</li><li>• Recycled content in plastic material</li><li>• Privacy Filter Slot</li><li>• Microsoft<sup>®</sup> Windows<sup>®</sup> 7 certified</li></ul>				<b>ThinkVision LT1952p Wide Monitor</b>	
Name	<b>LT1952p Wide Flat Panel Monitor</b>																																																																																											
Case color	<b>Business black</b>																																																																																											
Type-model	<b>2448-MB6</b>																																																																																											
Panel	TFT-LCD, twisted nematic (TN), White LED backlight																																																																																											
Viewable image size	<b>19" (482.6mm)</b> diagonal																																																																																											
Max view area (W x H)	16.07" x 10.05" (408.2mm x 255.2mm)																																																																																											
Optimum resolution	<b>1440x900</b>																																																																																											
Max pixel rate	137MHz																																																																																											
Aspect ratio	16:10																																																																																											
Pixel pitch (mm)	0.2835mm																																																																																											
Dot/Pixel per Inch	89.4 dpi																																																																																											
Brightness	250 nits or cd/m <sup>2</sup> (typical)																																																																																											
Contrast ratio	1000:1 (typical)																																																																																											
Pixel response time	5ms (typical)																																																																																											
Color gamut	72%																																																																																											
Anti-reflective	Anti-reflective, anti-glare																																																																																											
Viewing angle at 10:1 CR	170° horizontal, 160° vertical																																																																																											
Stand	Tilt, swivel, and height adjustable stand																																																																																											
Bezel width	<i>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</i>																																																																																											
Dimensions (HxWxD)	15.66-19.99" H x 17.36" W x 6.74" D; 397.7-507.7mm H x 440.9mm W x 171.3mm D																																																																																											
Power supply	13 watts typical, 17 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)																																																																																											
Weight	9.49 lb; 4.30kg																																																																																											
Limited warranty <sup>4</sup>	<b>3 year</b> (includes backlight)																																																																																											
Available date	September 2011																																																																																											
VESA-compliant <sup>2</sup>	VESA DDC2B/CI																																																																																											
Power management	ENERGY STAR <sup>®</sup> 5.1																																																																																											
Ergonomics	ISO 9241-307																																																																																											
Emission standards	MPR-2, FCC Class B																																																																																											
Environmental	TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b> , ULE Gold																																																																																											
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1366x768 WXGA+: 1440x900																																																																																											
Presets / user settings	Standard presets: 22; user settings: 22																																																																																											
Viewing adjustments	<i>Tilt: 20° back, -3° forward; lift: 4.3" (110mm); swivel: +/-180°; detachable stand</i>																																																																																											
Rotating screen	None																																																																																											
On screen display	On screen display with digital user controls (8 languages)																																																																																											
Control features	Direct access (buttons on front) for automatic image setup, input switch, and brightness																																																																																											
Multiple input	Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)																																																																																											
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, HDCP-compliant (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>																																																																																											
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)																																																																																											
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI <sup>®</sup> (100mm mount)																																																																																											
Security	Security keyhole for attachment of optional cable lock (Kensington <sup>®</sup> lock-compatible)																																																																																											
Ship group	Monitor, attached stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord																																																																																											
Features																																																																																												
<ul style="list-style-type: none"><li>• Widescreen 19-inch monitor</li><li>• Supports 1440x900 resolution</li><li>• Ergonomic stand tilts, swivel, and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Cable Management for better user experience</li><li>• Mercury and arsenic free glass</li><li>• Recycled content in plastic material</li><li>• Privacy Filter Slot</li><li>• Microsoft<sup>®</sup> Windows<sup>®</sup> 7 certified</li></ul>																																																																																												
																																																																																												
<b>ThinkVision LT1952p Wide Monitor</b>																																																																																												
<table><tr><th colspan="2">Limited Warranty</th></tr><tr><td colspan="2"><ul style="list-style-type: none"><li>⇒ <b>3 year limited warranty<sup>4</sup></b></li><li>⇒ <b>International Warranty Service<sup>5</sup></b></li><li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li><li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li><li>⇒ <b>Service upgrade options:<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></li><li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li></ul></td></tr></table>	Limited Warranty		<ul style="list-style-type: none"><li>⇒ <b>3 year limited warranty<sup>4</sup></b></li><li>⇒ <b>International Warranty Service<sup>5</sup></b></li><li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li><li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li><li>⇒ <b>Service upgrade options:<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></li><li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li></ul>		<table><tr><th colspan="2">Accessories</th></tr><tr><td>DisplayPort to DisplayPort Monitor Cable</td><td>0A36537</td></tr><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr><tr><td>ThinkCentre Extend Arm</td><td>57Y4352</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr><tr><td colspan="2">See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></td></tr><tr><td colspan="2">See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></td></tr></table>	Accessories		DisplayPort to DisplayPort Monitor Cable	0A36537	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258	See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>		See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>																																																																						
Limited Warranty																																																																																												
<ul style="list-style-type: none"><li>⇒ <b>3 year limited warranty<sup>4</sup></b></li><li>⇒ <b>International Warranty Service<sup>5</sup></b></li><li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li><li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li><li>⇒ <b>Service upgrade options:<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></li><li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li></ul>																																																																																												
Accessories																																																																																												
DisplayPort to DisplayPort Monitor Cable	0A36537																																																																																											
Kensington MicroSaver Cable Lock	73P2582																																																																																											
Kensington Twin Head Cable Lock	45K1620																																																																																											
Lenovo Security Cable Lock	57Y4303																																																																																											
ThinkCentre Extend Arm	57Y4352																																																																																											
Lenovo Easy Reach Monitor Stand	55Y9258																																																																																											
See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>																																																																																												
See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>																																																																																												





<p> <b>Name</b> LT1953 Wide Flat Panel Monitor  <b>Case color</b> Business black  <b>Type-model</b> 1453-HB1 (Latin America)  <b>Panel</b> TFT-LCD, twisted nematic (TN), White LED backlight  <b>Viewable image size</b> 19" (482.6mm) diagonal  <b>Max view area (W x H)</b> 16.07" x 10.05" (408.2mm x 255.2mm)  <b>Optimum resolution</b> 1440x900  <b>Max pixel rate</b> 205MHz(VGA), 165MHz(DVI)  <b>Aspect ratio</b> 16:10  <b>Pixel pitch (mm)</b> 0.2835mm  <b>Dot/Pixel per Inch</b> 89.4 dpi  <b>Brightness</b> 250 nits or cd/m<sup>2</sup> (typical)  <b>Contrast ratio</b> 1000:1 (typical)  <b>Pixel response time</b> 5ms (typical)  <b>Color gamut</b> 72%  <b>Viewing angle at 10:1 CR</b> 170° horizontal, 160° vertical  <b>Stand</b> Tilt stand  <b>Bezel width</b> Sides: 0.66" (16.8mm); top: 0.66" (16.8mm); bottom: 0.66" (16.8mm)  <b>Dimensions (HxWxD, excluding stand)</b> 290.2mm H x 443.2mm W x 50.5mm D  <b>Dimensions (HxWxD, including stand)</b> 354.0mm H x 443.2mm W x 160.7mm D  <b>Power supply</b> 17 watts typical, 20 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)  <b>Weight</b> 6.61 lb; 3.00kg  <b>Limited warranty<sup>4</sup></b> 3 year (includes backlight)  <b>Available date</b> March 2013                 </p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 19-inch monitor</li> <li>• Supports 1440x900 resolution</li> <li>• VGA and DVI connections</li> <li>• Arsenic free glass</li> <li>• Support Lenovo Tiny PC via VESA mount</li> <li>• 85% PCC plastic resins</li> <li>• Microsoft® Windows® 7 certified</li> <li>• Microsoft Windows 8 certified</li> </ul>						
<p> <b>VESA-compliant<sup>2</sup></b> VESA DDC2B/CI  <b>Power management</b> ENERGY STAR® 6.0  <b>Ergonomics</b> ISO 9241-307  <b>Emission standards</b> MPR-2, FCC Class B  <b>Environmental</b> TCO Displays 6.0, TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b>, ULE Gold  <b>Preset resolutions</b> VGA: 640x350, 640x480, 720x400                                                      SVGA: 800x600, 832x624                                                      XGA: 1024x768, 1152x864                                                      SXGA: 1280x1024                                                      WXGA+: 1440x900  <b>Presets / user settings</b> Standard presets: 20;                        user settings: 20                 </p>	 <p><b>ThinkVision LT1953 Wide Monitor</b></p>						
<p> <b>Viewing adjustments</b> Tilt: 22° back, -5° forward  <b>Rotating screen</b> None  <b>On screen display</b> On screen display with digital user controls (8 languages)  <b>Control features</b> Direct access (buttons on front) for automatic image setup, input switch, and brightness  <b>Multiple input</b> Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)  <b>Monitor connectors</b> (1) VGA 15-pin D-shell, analog, blue                                                      (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>  <b>Signal cables</b> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                                                      (2) detachable, DVI-D at each end, digital, 1.8 meter  <b>Mounting features</b> Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)  <b>Security</b> Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)                 </p>							
<p><b>Ship group</b> Monitor, tilt stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</p>							
<p><b>Limited Warranty</b></p> <p>                     ➤ 3 year limited warranty<sup>4</sup>                      ➤ International Warranty Service<sup>5</sup>                      ➤ Replacement normally arrives in two business days, excluding holidays                      ➤ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup>                      ➤ Service upgrade options:<sup>7</sup> <ul style="list-style-type: none"> <li>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209)</li> <li>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</li> <li>• 4 year, mail exchange (51J0589)</li> <li>• 5 year, mail exchange (51J0590)</li> </ul>                     ➤ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup> </p>	<p><b>Accessories</b></p> <table> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303
Kensington MicroSaver Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						
Lenovo Security Cable Lock	57Y4303						

<p>Name <b>LT2013p Wide Flat Panel Monitor</b>                  Case color <b>Business black</b>                  Type-model <b>60A0MAR1US</b>                  Panel <b>TFT-LCD, twisted nematic (TN), White LED backlight</b>                  Viewable image size <b>19.5" (494mm) diagonal</b>                  Max view area (W x H) <b>17.05" x 9.44" / 433.0mm x 239.8mm</b>                  Optimum resolution <b>1600x900</b>                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>.27mm</b>                  Dot/Pixel per Inch <b>94 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt, swivel, pivot, and height adjustable stand (toolless detachable)</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 19.5-inch monitor</li> <li>• HD support, HDCP-compliant</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Compliance with ENERGY STAR 6.0</li> <li>• Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket</li> <li>• Arsenic/Lead/Mercury free</li> <li>• EPEAT Gold certified</li> <li>• Microsoft® Windows® 7 certified</li> <li>• Microsoft Windows 8 certified</li> </ul>										
<p>Bezel width  <i>Sides:</i> 0.66" (16.8mm);  <i>top:</i> 0.66" (16.8mm);  <i>bottom:</i> 0.66" (16.8mm)</p> <p>Dimensions                  (HxWxD, excluding stand) 274.8mm H x 467.0mm W x 52.8mm D                  (HxWxD, including stand) 336.5mm H x 467.0mm W x 200.0mm D</p> <p>Power supply                  17 watts typical, 36 watts maximum,                  &lt;1.0 watts sleep/off (w/o USB hub);                  &lt;0.5 watts switch off (w/o USB hub)                  integrated (no external brick-like power supply)</p> <p>Weight                  9.70 lb; 4.40kg (excluding stand)</p> <p>Limited warranty<sup>4</sup>  <b>3 year</b> (includes backlight)</p> <p>Available date                  March 2013</p>	 <p><b>ThinkVision LT2013p Wide Monitor</b></p>										
<p>VESA-compliant<sup>2</sup>                  Power management                  Ergonomics                  Emission standards                  Environmental</p> <p>VESA DDC2B/CI, VESA DPMS-compliant                  ENERGY STAR® 6.0                  ISO 9241-307                  MPR-2, FCC Class B                  TCO Displays 6.0, TCO Certified Edge 1.1, RoHS,  <b>EPEAT™ Gold rating</b></p>	<p>Preset resolutions                  VGA: 640x350, 640x480, 720x400                  SVGA: 800x600, 832x624                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1366x768                  WXGA+: 1440x900                  WSXGA+: 1600x900</p> <p>Presets / user settings                  Presets: 24; user settings: 24</p>										
<p>Viewing adjustments                  Rotating screen</p> <p>On screen display                  Control features                  USB hub                  Multiple input                  Monitor connectors</p> <p>Signal cables                  Mounting features                  Security</p>	<p><b>Tilt:</b> 30° back, -5° forward; <b>lift:</b> 4.3" (110mm); <b>swivel:</b> +/-45°; detachable stand  <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller, do not support image rotation under dual image modes)                  On screen display with digital user controls (8 languages)                  Direct access (buttons on front) for automatic image setup, input switch, and brightness                  USB 2.0 Hub (1 port into PC, 4 ports for accessories)                  Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)                  (1) VGA 15-pin D-shell, analog, blue                  (2) DisplayPort, digital, black, <b>HDCP-compliant</b>                  (3) HDMI (1.4), digital, <b>HDCP-compliant</b>                  (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)                  Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>										
<p>Ship group</p>	<p>Monitor, toolless detachable stand, Quick start and safety poster, analog signal cable, 1.8 meter USB cable, 1.8 meter black power cord</p>										
<p><b>Limited Warranty</b></p> <p>⇒ <b>3 year limited warranty<sup>4</sup></b>                  ⇒ <b>International Warranty Service<sup>5</sup></b>                  ⇒ <b>Replacement normally arrives in two business days, excluding holidays</b>                  ⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b>                  ⇒ <b>Service upgrade options<sup>7</sup></b></p> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> <p>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></p>	<p><b>Accessories</b></p> <table> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington MicroSaver Cable Lock	73P2582										
Kensington Twin Head Cable Lock	45K1620										
Lenovo Security Cable Lock	57Y4303										
Lenovo Easy Reach Monitor Stand	55Y9258										
ThinkCentre Extend Arm	57Y4352										




<div>Name</div> <div>Case color</div> <div>Type-model</div> <div>Panel</div> <div>Viewable image size</div> <div>Max view area (W x H)</div> <div>Optimum resolution</div> <div>Aspect ratio</div> <div>Pixel pitch (mm)</div> <div>Dot/Pixel per Inch</div> <div>Brightness</div> <div>Contrast ratio</div> <div>Pixel response time</div> <div>Color gamut</div> <div>Viewing angle at 10:1 CR</div> <div>Stand</div> <div>Bezel width</div> <div>Dimensions</div> <div>(HxWxD, excluding stand)</div> <div>Dimensions</div> <div>(HxWxD, including stand)</div> <div>Power supply</div> <div>Weight</div> <div>Limited warranty<sup>4</sup></div> <div>Available date</div>	<div>LT2013s Wide Flat Panel Monitor</div> <div>Business black</div> <div>60ABAAR1US</div> <div>TFT-LCD, twisted nematic (TN), White LED backlight</div> <div>19.5" (494mm) diagonal</div> <div>17.08" x 9.30" / 433.9mm x 236.3mm</div> <div>1600x900</div> <div>16:9</div> <div>.27 (H) x .26 (V) mm</div> <div>281/94 dpi</div> <div>200 nits or cd/m<sup>2</sup> (typical)</div> <div>600:1 (typical)</div> <div>5ms (typical)</div> <div>72%</div> <div>90° (+/- 45°) horizontal, 50° (+ 15/- 35°) vertical</div> <div>Tilt stand</div> <div>Sides: 0.62" (15.85mm);</div> <div>top: 0.73" (18.55mm);</div> <div>bottom: 0.73" (18.55mm)</div> <div>10.83" H x 18.41" W x 2.09" D;</div> <div>274.8mm H x 467.0mm W x 53.0mm D</div> <div>13.50" H x 18.41" W x 6.33" D;</div> <div>342.4mm H x 467.0mm W x 160.7mm D</div> <div>17 watts typical, 19 watts maximum,</div> <div>&lt;0.5 watts sleep/off;</div> <div>&lt;0.5 watts switch off</div> <div>integrated (no external brick-like power supply)</div> <div>5.50 lb; 2.50kg (excluding stand)</div> <div>3 year (includes backlight)</div> <div>July 2013</div>	<div>Features</div> <div>• Widescreen 19.5-inch monitor</div> <div>• Compliance with ENERGY STAR 6.0</div> <div>• Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket</div> <div>• EPEAT Silver certified</div> <div>• Microsoft® Windows® 7 certified</div> <div>• Microsoft Windows 8 certified</div>
<div>VESA-compliant<sup>2</sup></div> <div>Power management</div> <div>Ergonomics</div> <div>Emission standards</div> <div>Environmental</div> <div>Preset resolutions</div> <div>SVGA:</div> <div>XGA:</div> <div>SXGA:</div> <div>WXGA:</div> <div>WXGA+:</div> <div>WSXGA+:</div> <div>Presets / user settings</div>	<div>VESA DDC2B/CI, EDID 1.3</div> <div>ENERGY STAR® 6.0</div> <div>ISO 9241-307</div> <div>FCC Class B</div> <div>RoHS, EPEAT™ Silver rating</div> <div>VGA: 640x350, 640x480, 720x400</div> <div>800x600, 832x624</div> <div>1024x768, 1152x864</div> <div>1280x1024</div> <div>1366x768</div> <div>1440x900</div> <div>1600x900</div> <div>Presets: 24; user settings: 24</div>	<div></div> <div>ThinkVision LT2013s Wide Monitor</div>
<div>Viewing adjustments</div> <div>Rotating screen</div> <div>On screen display</div> <div>Control features</div> <div>USB hub</div> <div>Multiple input</div> <div>Monitor connectors</div> <div>Signal cables</div> <div>Mounting features</div> <div>Security</div>	<div>Tilt: 22° back, -5° forward</div> <div>None</div> <div>On screen display with digital user controls (8 languages)</div> <div>Direct access (buttons on front) for automatic image setup, input switch, and brightness</div> <div>None</div> <div>VGA input</div> <div>(1) VGA 15-pin D-shell, analog, blue</div> <div>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>	
<div>Ship group</div>	<div>Monitor, stand and base, Quick start and safety poster, analog signal cable, 1.8 meter black power cord</div>	
<div>Limited Warranty</div> <div>See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a></div>		
<div>Accessories</div> <div><div>Kensington MicroSaver Cable Lock</div><div>73P2582</div></div> <div><div>Kensington Twin Head Cable Lock</div><div>45K1620</div></div> <div><div>Lenovo Security Cable Lock</div><div>57Y4303</div></div> <div><div>Lenovo Easy Reach Monitor Stand</div><div>55Y9258</div></div> <div><div>ThinkCentre Extend Arm</div><div>57Y4352</div></div>		
<div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div>		
<div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>		


<div>Name Case color Type-model Panel Viewable image size Max view area (W x H) Native resolution Aspect ratio Pixel pitch (mm) Dot/Pixel per Inch Brightness Contrast ratio Pixel response time Color gamut Viewing angle at 10:1 CR Stand Bezel width Dimensions (HxWxD)  Power supply  Weight Limited warranty<sup>4</sup> Available date</div>		<div>LT2024 Wide Flat Panel Monitor Business black 60B9HAR1US TFT-LCD, twisted nematic (TN), White LED backlight 20.0" (508mm) diagonal 17.4" x 9.8" (442.8mm x 249.1mm) 1600x900 16:9 .276mm 92 dpi 250 nits or cd/m<sup>2</sup> (typical) 1000:1 (typical) 5ms (typical) 72% 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt adjustable stand Sides: 0.567" (14.4mm) 13.68" H x 18.83" W x 6.33" D; 347.4mm H x 478.4mm W x 160.7mm D 19 watts typical, 22 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 6.75 lb; 3.07 kg 3 year (includes backlight) March 2014</div>	<div>Features<ul style="list-style-type: none"><li>• Widescreen 20-inch monitor</li><li>• Supports 1600x900 resolution</li><li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li><li>• Arsenic / Mercury free glass</li><li>• EPEAT Gold certified</li><li>• Support Lenovo Tiny PC and 3rd party thin client</li><li>• Microsoft® Windows® 7 certified</li><li>• Microsoft Windows 8 / Windows 8.1 certified</li></ul></div>				
<div>VESA-compliant<sup>2</sup> Power management Ergonomics Emission standards Environmental</div>		<div>VESA DDC2B/CI ENERGY STAR® qualified ISO 9241-307 FCC Class B TCO Displays 6.0, TCO Certified Edge 1.2, WEEE, RoHS, EPEAT™ Gold rating</div>	<div> <b>ThinkVision LT2024 Wide Monitor</b></div>				
<div>Preset resolutions  Presets / user settings</div>		<div>VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900 Standard presets: 24 user settings: 24</div>					
<div>Viewing adjustments Rotating screen On screen display Control features Multiple input Monitor connectors  Signal cables Mounting features Security</div>		<div>Tilt: 22° backward, -5° forward None On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, dual input and brightness Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>					
<div>Ship group</div>		<div>Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter black power cord</div>					
<div>Limited Warranty See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a></div>		<div>Accessories</div> <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr></table> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>		Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						

<p>Name <b>ThinkVision LT2223p 21.5-inch FHD LED Backlit LCD Monitor</b></p> <p>Case color <b>Business black</b></p> <p>Type-model <b>60A1MAR2US</b></p> <p>Panel TFT-LCD, twisted nematic (TN), White LED backlight</p> <p>Viewable image size <b>21.5" (546mm)</b> diagonal</p> <p>Max view area (W x H) <b>18.74" x 10.54" / 476.1mm x 267.8mm</b></p> <p>Optimum resolution <b>1920x1080</b></p> <p>Aspect ratio 16:9</p> <p>Pixel pitch (mm) 0.248mm</p> <p>Dot/Pixel per Inch 103 dpi</p> <p>Brightness 250 nits or cd/m<sup>2</sup> (typical)</p> <p>Contrast ratio 1000:1 (typical)</p> <p>Dynamic Contrast ratio 2000000:1</p> <p>Pixel response time 5ms (typical)</p> <p>Color gamut 72%</p> <p>Viewing angle at 10:1 CR 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</p> <p>Stand Tilt, swivel, pivot, and height adjustable stand (toolless detachable)</p> <p>Bezel width <i>Sides:</i> 0.68" (17.3mm); <i>top:</i> 0.68" (17.3mm); <i>bottom:</i> 0.68" (17.3mm)</p> <p>Dimensions (HxWxD, excluding stand) 304.1mm H x 512.6mm W x 56.4mm D</p> <p>Dimensions (HxWxD, including stand) 362.9mm H x 512.6mm W x 218.4mm D</p> <p>Power supply 23 watts typical, 27 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</p> <p>Weight (including stand) 10.94 lb; 4.96kg</p> <p>Weight (Head only) 6.77 lb; 3.07kg</p> <p>Limited warranty<sup>4</sup> <b>3 year</b> (includes backlight)</p> <p>Available date March 2013</p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 21.5-inch monitor</li> <li>• 1080p full HD support</li> <li>• Integrated USB Hub (4 USB 2.0)</li> <li>• Supports VGA, DisplayPort 1.2 and HDMI 1.4 interfaces (HDCP-compliant)</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Compliance with ENERGY STAR 6.0</li> <li>• Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket</li> <li>• Arsenic/Lead/Mercury free</li> <li>• EPEAT Gold certified</li> <li>• Microsoft® Windows® 7 certified</li> <li>• Microsoft Windows 8 certified</li> </ul>
<p>VESA-compliant<sup>2</sup> VESA DDC2B/CI, VESA DPMS-compliant</p> <p>Power management ENERGY STAR® 6.0</p> <p>Ergonomics ISO 9241-307</p> <p>Emission standards MPR-2, FCC Class B</p> <p>Environmental TCO Displays 6.0, TCO Certified Edge 1.1, RoHS, <b>EPEAT™ Gold rating</b></p>	 <p><b>ThinkVision LT2223p Wide Monitor</b></p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>
<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>	<p>Preset resolutions</p> <p>VGA: 640x350, 640x480, 720x400</p> <p>SVGA: 800x600, 832x624</p> <p>XGA: 1024x768, 1152x864</p> <p>SXGA: 1280x1024</p> <p>WXGA: 1366x768</p> <p>WXGA+: 1440x900</p> <p>WSXGA+: 1600x900, 1680x1050</p> <p>Full HD: 1920x1080</p>

<b>Name</b> <b>Case color</b> <b>Type-model</b> <b>Panel</b> <b>Viewable image size</b> <b>Max view area (W x H)</b> <b>Optimum resolution</b> <b>Aspect ratio</b> <b>Pixel pitch (mm)</b> <b>Dot/Pixel per Inch</b> <b>Brightness</b> <b>Contrast ratio</b> <b>Dynamic Contrast ratio</b> <b>Pixel response time</b> <b>Color gamut</b> <b>Viewing angle at 10:1 CR</b> <b>Stand</b> <b>Bezel width</b> <b>Dimensions (HxWxD, excluding stand)</b> <b>Dimensions (HxWxD, including stand)</b> <b>Power supply</b> <b>Weight (including stand)</b> <b>Weight (Head only)</b> <b>Limited warranty<sup>4</sup></b> <b>Available date</b>		<b>ThinkVision LT2223z</b> <b>21.5-inch FHD LED Backlit LCD VoIP Monitor</b> <b>Business black</b> <b>60A2MAR2US</b> TFT-LCD, twisted nematic (TN), White LED backlight <b>21.5" (546mm)</b> diagonal 18.74" x 10.54" / 476.1mm x 267.8mm <b>1920x1080</b> 16:9 0.248mm 103 dpi 250 nits or cd/m <sup>2</sup> (typical) 1000:1 (typical) 2000000:1 5ms (typical) 72% 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt, swivel, pivot, and height adjustable stand (toolless detachable) <i>Sides:</i> 0.68" (17.3mm); <i>top:</i> 1.33" (33.8mm); <i>bottom:</i> 1.88" (47.8mm) 13.82" H x 20.18" W x 2.12" D; 351.1mm H x 512.6mm W x 56.4mm D 14.94" H x 20.18" W x 8.60" D; 379.4mm H x 512.6mm W x 218.4mm D 24 watts typical, 28 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply) 11.98 lb; 5.43kg 7.79 lb; 3.53kg <b>3 year</b> (includes backlight) April 2013	<b>Features</b> <ul style="list-style-type: none"><li>• Widescreen 21.5-inch monitor</li><li>• 1080p full HD support</li><li>• Integrated camera (FHD), speakers &amp; dual digital microphone</li><li>• Integrated USB 3.0 Hub (2 USB 3.0)</li><li>• Supports VGA, DisplayPort 1.2 and HDMI 1.4 interfaces (HDCP-compliant)</li><li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Compliance with ENERGY STAR 6.0</li><li>• Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket</li><li>• Arsenic/Lead/Mercury free</li><li>• EPEAT Gold certified</li><li>• Microsoft® Windows® 7 certified</li><li>• Microsoft Windows 8 certified</li></ul>									
<b>VESA-compliant<sup>2</sup></b> <b>Power management</b> <b>Ergonomics</b> <b>Emission standards</b> <b>Environmental</b> <b>Preset resolutions</b> <b>Presets / user settings</b>	VESA DDC2B/CI, VESA DPMS-compliant ENERGY STAR® 6.0 ISO 9241-307 MPR-2, FCC Class B TCO Displays 6.0, TCO Certified Edge 1.1, RoHS, <b>EPEAT™ Gold rating</b> VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900 WSXGA+: 1600x900, 1600x1050 Full HD: 1920x1080 Presets: 25; user settings: 20	 <b>ThinkVision LT2223z Wide Monitor</b>										
<b>Viewing adjustments</b> <b>Rotating screen</b> <b>On screen display</b> <b>Control features</b> <b>USB hub</b> <b>Multimedia</b> <b>Camera</b> <b>Multiple input</b> <b>Monitor connectors</b> <b>Signal cables</b> <b>Mounting features</b> <b>Security</b> <b>Ship group</b>	<i>Tilt:</i> 30° back, -5° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller, do not support image rotation under dual image modes) On screen display with digital user controls (8 languages) Direct access (buttons on front) for MIC mute, speaker mute and hook switch buttons USB 3.0 Hub: 1 port into PC (USB 3.0); 2 ports for accessories (2 USB 3.0) Integrated digital speakers (3 watts x 2) Integrated camera (FHD) and digital dual microphone array, with Camera lock button for security Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort (1.2), digital, black, <b>HDCP-compliant</b> (3) HDMI (1.4), digital, <b>HDCP-compliant</b> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible) Monitor, toolless detachable stand, Quick start and safety poster, analog signal cable, 1.8 meter USB 3.0 cable, 1.8 meter black power cord											
<b>Limited Warranty</b> <ul style="list-style-type: none"><li>⇒ <b>3 year limited warranty<sup>4</sup></b></li><li>⇒ <b>International Warranty Service<sup>5</sup></b></li><li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li><li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li><li>⇒ <b>Service upgrade options:<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></li><li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li></ul>			<b>Accessories</b> <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr><tr><td>ThinkCentre Extend Arm</td><td>57Y4352</td></tr></table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm
Kensington MicroSaver Cable Lock	73P2582											
Kensington Twin Head Cable Lock	45K1620											
Lenovo Security Cable Lock	57Y4303											
Lenovo Easy Reach Monitor Stand	55Y9258											
ThinkCentre Extend Arm	57Y4352											



<p>Name <b>LT2252p Wide Flat Panel Monitor</b>                  Case color <b>Business black</b>                  Type-model <b>2572-MB6 / 2572-MB1</b>                  Panel TFT-LCD, twisted nematic (TN), White LED backlight                  Viewable image size <b>22" (559mm)</b> diagonal                  Max view area (W x H) <b>18.7" x 11.7"</b> (473.8mm x 296.1mm)                  Optimum resolution <b>1680x1050</b>                  Max pixel rate 205MHz                  Aspect ratio 16:10                  Pixel pitch (mm) 0.282mm                  Dot/Pixel per Inch 90 dpi                  Brightness 250 nits or cd/m<sup>2</sup> (typical)                  Contrast ratio 1000:1 (typical)                  Pixel response time 5ms (typical)                  Color gamut 72%                  Anti-reflective Anti-reflective, anti-glare                  Viewing angle at 10:1 CR 170° horizontal, 160° vertical                  Stand Tilt, swivel, pivot, and height adjustable stand                  Bezel width <i>Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm)</i></p> <p>Dimensions (HxWxD) 14.46-18.79" H x 19.92" W x 9.50" D;                  367.3-477.3mm H x 506mm W x 241.2mm D</p> <p>Power supply 20 watts typical, 26 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)                  12.97lb; 5.89kg</p> <p>Weight 12.97lb; 5.89kg                  Limited warranty<sup>4</sup> <b>3 year</b> (includes backlight)                  Available date September 2011 / December 2012</p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 22-inch monitor</li> <li>• Supports 1680x1050 resolution</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Cable Management for better user experience</li> <li>• Mercury and arsenic free glass</li> <li>• Recycled content in plastic material</li> <li>• Privacy Filter Slot</li> <li>• Microsoft® Windows® 7 certified</li> <li>• Model 2572-MB1 supports Lenovo Tiny PC via optional Lenovo bracket</li> </ul>												
<p>VESA-compliant<sup>2</sup> VESA DDC2B/CI                  Power management ENERGY STAR® 5.1 (2572-MB6)                  ENERGY STAR® 6.0 (2572-MB1)                  Ergonomics ISO 9241-307                  Emission standards MPR-2, FCC Class B                  Environmental TCO Displays 5.2, TCO Certified Edge 1.1,                  WEEE, RoHS, <b>EPEAT™ Gold rating</b>, ULE Gold</p> <p>Preset resolutions                  VGA: 640x350, 640x480, 720x400                  SVGA: 800x600                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x768, 1280x800, 1366x768                  WXGA+: 1440x900                  1600x900                  WSXGA+: 1680x1050</p> <p>Presets / user settings                  Standard presets: <i>VGA/DisplayPort: 26; DVI-D: 25;</i>                  user settings: 25</p>	 <p><b>ThinkVision LT2252p Wide Monitor</b></p>												
<p>Viewing adjustments <i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i>                  Rotating screen <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller)                  On screen display On screen display with digital user controls (8 languages)                  Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness                  USB hub None                  Camera None                  Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)                  Monitor connectors (1) VGA 15-pin D-shell, analog, blue                  (2) DisplayPort, digital, black, <b>HDCP-compliant</b>                  (3) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  (2) detachable, DVI-D at each end, digital, 1.8 meter                  Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)                  Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)                  Mounting features Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)                  Security</p> <p>Ship group Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable,                  1.8 meter DVI-D cable, 1.8 meter black power cord</p>													
<p><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>3 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>International Warranty Service<sup>5</sup></b></li> <li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> </li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p><b>Accessories</b></p> <table> <tr> <td>DisplayPort to DisplayPort Monitor Cable</td> <td>0A36537</td> </tr> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	DisplayPort to DisplayPort Monitor Cable	0A36537	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
DisplayPort to DisplayPort Monitor Cable	0A36537												
Kensington MicroSaver Cable Lock	73P2582												
Kensington Twin Head Cable Lock	45K1620												
Lenovo Security Cable Lock	57Y4303												
ThinkCentre Extend Arm	57Y4352												
Lenovo Easy Reach Monitor Stand	55Y9258												

Name	LT2323p Wide Flat Panel Monitor	<b>Features</b> <ul style="list-style-type: none"><li>• Widescreen 23-inch monitor</li><li>• 1080p full HD support, HDCP-compliant</li><li>• Built-in VGA, DVI and DisplayPort connectors for attachment to three systems concurrently</li><li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Compliance with ENERGY STAR 6.0 DRAFT</li><li>• Microsoft® Windows® 7 certified</li></ul>
Case color	Raven black	
Type-model	3024-HC1	 <p><b>ThinkVision LT2323p Wide Monitor</b></p>
Panel	TFT-LCD, twisted nematic (TN), White LED backlight	
Viewable image size	23.0" (584mm) diagonal	
Max view area (W x H)	18.65" x 11.66" / 473.8mm x 296.1mm	
Optimum resolution	1920x1080	
Aspect ratio	16:9	
Pixel pitch (mm)	.265mm	
Dot/Pixel per Inch	96 dpi	
Brightness	250 nits or cd/m² (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	5ms (typical)	
Color gamut	72%	
Anti-reflective	Anti-reflective, anti-glare	
Vertical frequency	50 to 75Hz	
Horizontal frequency	30 to 83kHz	
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical	
Stand	Tilt, swivel, pivot, and height adjustable stand (toolless detachable)	
Bezel width	Sides: 0.68" (17.2mm); top: 0.70" (17.7mm); bottom: 0.94" (24.0mm)	
Dimensions (HxWxD)	14.66" H x 21.49" W x 2.06" D; (excluding stand) 372.3mm H x 546.0mm W x 52.3mm D	
Power supply	20 watts typical, 38 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)	
Weight	12.65 lb; 5.74kg (excluding stand)	
Limited warranty <sup>4</sup>	3 year (includes backlight)	
Available date	May 2012	
VESA-compliant <sup>2</sup>	VESA DDC2B/CI, VESA DPMS-compliant	
Power management	ENERGY STAR® 6.0 DRAFT	
Ergonomics	ISO 9241-307	
Emission standards	MPR-2, FCC Class B	
Environmental	TCO (TCO Certified Edge 1.1), WEEE, RoHS, <b>EPEAT™ Gold rating</b>	
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1360x768 WXGA+: 1440x900 WSXGA+: 1680x1050 Full HD: 1920x1080	
Presets / user settings	Presets: 26; user settings: 25	
Viewing adjustments	Tilt: 30° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand	
Rotating screen	Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller, do not support image rotation under dual image modes)	
On screen display	On screen display with digital user controls (8 languages)	
Control features	Direct access (buttons on front) for automatic image setup, input switch, and brightness	
USB hub	USB 2.0 Hub (1 port into PC, 4 ports for accessories)	
Multiple input	Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)	
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, <b>HDCP-compliant</b> (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>	
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)	
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group	Monitor, toolless detachable stand, Quick start and safety poster, analog signal cable, DVI-D cable, 1.8 meter USB cable, 1.8 meter black power cord	
<b>Limited Warranty</b>		<b>Accessories</b>
⇒ 3 year limited warranty <sup>4</sup>		<b>I I M I B</b>
⇒ International Warranty Service <sup>5</sup>		Kensington MicroSaver Cable Lock 73P2582
⇒ Replacement normally arrives in two business days, excluding holidays		Kensington Twin Head Cable Lock 45K1620
⇒ Lenovo pays all shipping costs for valid warranty claims <sup>6</sup>		Lenovo Security Cable Lock 57Y4303
⇒ Service upgrade options: <sup>7</sup>		Lenovo Easy Reach Monitor Stand 55Y9258
• 3 year, on site exchange, Mon-Fri 9-5 with next day response (Lenovo Services part number 41C9209)		ThinkCentre Extend Arm 57Y4352
• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)		
• 4 year, mail exchange (51J0589)		
• 5 year, mail exchange (51J0590)		
⇒ 24x7 <sup>8</sup> day toll-free support for warranty issues during the warranty period <sup>4</sup>		
		See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>
		See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>




## ThinkVision LT2323z Wide Monitor

<p> <b>Name</b> LT2423 Wide Flat Panel Monitor  <b>Case color</b> Business black  <b>Type-model</b> 60A8KAR2US  <b>Panel</b> TFT-LCD, twisted nematic (TN), White LED backlight  <b>Viewable image size</b> 24" (610mm) diagonal  <b>Max view area (W x H)</b> 20.9" x 11.8" (531.4mm x 298.9mm)  <b>Optimum resolution</b> 1920x1080  <b>Max pixel rate</b> 205MHz  <b>Aspect ratio</b> 16:9  <b>Pixel pitch (mm)</b> 0.278mm  <b>Dot/Pixel per Inch</b> 92 dpi  <b>Brightness</b> 250 nits or cd/m<sup>2</sup> (typical)  <b>Contrast ratio</b> 1000:1 (typical)  <b>Contrast ratio</b> 2000000:1  <b>Pixel response time</b> 5ms  <b>Color gamut</b> 72%  <b>Viewing angle at 10:1 CR</b> 170° horizontal, 160° vertical  <b>Stand</b> Tilt stand  <b>Bezel width</b> Sides: 0.67" (17.0mm); top: 0.67" (17.0mm); bottom: 1.02" (26.0mm)  <b>Dimensions</b> 13.53" H x 22.33" W x 1.97" D;  <b>(HxWxD, excluding stand)</b> 343.7mm H x 567.1mm W x 50.0mm D  <b>Dimensions</b> 16.30" H x 22.33" W x 8.50" D;  <b>(HxWxD, including stand)</b> 414.3mm H x 567.1mm W x 216.7mm D  <b>Power supply</b> 21 watts typical, 31 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)  <b>Weight</b> 8.30 lb; 3.76kg  <b>Limited warranty<sup>4</sup></b> 3 year (includes backlight)  <b>Available date</b> July 2013                 </p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 24-inch monitor</li> <li>• Supports 1920x1080 resolution</li> <li>• Two 3W stereo speakers</li> <li>• Audio in (3.5mm)</li> <li>• Supports VGA and HDMI 1.4 interfaces</li> <li>• Support Lenovo Tiny PC and 3rd party thin client via optional Lenovo bracket</li> <li>• Microsoft® Windows® 8 certified</li> <li>• Arsenic/Lead/Mercury free</li> </ul>																
<p> <b>VESA-compliant<sup>2</sup></b> VESA DDC2B/CI  <b>Power management</b> ENERGY STAR® 6.0  <b>Ergonomics</b> ISO 9241-307  <b>Emission standards</b> MPR-2, FCC Class B  <b>Environmental</b> TCO Displays 6.0, TCO Certified Edge 1.2, WEEE, RoHS, <b>EPEAT™ Gold rating</b>, ULE Gold                 </p>	<div data-bbox="971 575 1471 1073" data-label="Image"> </div> <p><b>ThinkVision LT2423 Wide Monitor</b></p>																
<p> <b>Preset resolutions</b> <table border="0"> <tr><td>VGA:</td><td>640x350, 640x480, 720x400</td></tr> <tr><td>SVGA:</td><td>800x600, 832x624</td></tr> <tr><td>XGA:</td><td>1024x768, 1152x864</td></tr> <tr><td>SXGA:</td><td>1280x1024</td></tr> <tr><td>WXGA:</td><td>1366x768</td></tr> <tr><td>WXGA+:</td><td>1440x900, 1600x900</td></tr> <tr><td>WSXGA+:</td><td>1680x1050</td></tr> <tr><td>Full HD:</td><td>1920x1080</td></tr> </table> </p> <p> <b>Presets / user settings</b> Standard presets: 24; User settings: 20                 </p>	VGA:	640x350, 640x480, 720x400	SVGA:	800x600, 832x624	XGA:	1024x768, 1152x864	SXGA:	1280x1024	WXGA:	1366x768	WXGA+:	1440x900, 1600x900	WSXGA+:	1680x1050	Full HD:	1920x1080	
VGA:	640x350, 640x480, 720x400																
SVGA:	800x600, 832x624																
XGA:	1024x768, 1152x864																
SXGA:	1280x1024																
WXGA:	1366x768																
WXGA+:	1440x900, 1600x900																
WSXGA+:	1680x1050																
Full HD:	1920x1080																
<p> <b>Viewing adjustments</b> Tilt: 22° back, -5° forward  <b>Rotating screen</b> None  <b>On screen display</b> On screen display with digital user controls (8 languages)  <b>Control features</b> Direct access (buttons on front) for automatic image setup, input switch, and brightness  <b>Multimedia</b> Integrated stereo speakers (3 watts x 2)  <b>Multiple input</b> Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)  <b>Monitor connectors</b> (1) VGA 15-pin D-shell, analog, blue                      (2) HDMI (1.4), digital, <b>HDCP-compliant</b>  <b>Signal cables</b> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter  <b>Mounting features</b> Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)  <b>Security</b> Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)                 </p>																	
<p> <b>Ship group</b> Monitor, attached stand, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter Audio cable, 1.8 meter black power cord                 </p>																	
<p> <b>Limited Warranty</b>                      See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a> </p>	<p> <b>Accessories</b> <table border="0"> <tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr> <tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr> <tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr> <tr><td>ThinkCentre Extend Arm</td><td>57Y4352</td></tr> <tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr> </table> </p> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258						
Kensington MicroSaver Cable Lock	73P2582																
Kensington Twin Head Cable Lock	45K1620																
Lenovo Security Cable Lock	57Y4303																
ThinkCentre Extend Arm	57Y4352																
Lenovo Easy Reach Monitor Stand	55Y9258																


<div>Name<b>LT2452p Wide Flat Panel Monitor</b></div> <div>Case color<b>Business black</b></div> <div>Type-model<b>4420-MB2 / 60A6MAR2US</b></div> <div>PanelTFT-LCD, e-IPS, White LED backlight</div> <div>Viewable image size<b>24" (610mm)</b> diagonal</div> <div>Max view area (W x H)20.4" x 12.8" (518.4mm x 324.0mm)</div> <div>Optimum resolution<b>1920x1200</b></div> <div>Max pixel rate202.5MHz</div> <div>Aspect ratio16:10</div> <div>Pixel pitch (mm)0.270mm</div> <div>Dot/Pixel per Inch94 dpi</div> <div>Brightness300 nits or cd/m<sup>2</sup> (typical)</div> <div>Contrast ratio1000:1 (typical)</div> <div>Pixel response time7ms (GtG)</div> <div>Color gamut72%</div> <div>Anti-reflectiveAnti-reflective, anti-glare</div> <div>Viewing angle at 10:1 CR178° horizontal, 178° vertical</div> <div>StandTilt, swivel, pivot, and height adjustable stand</div> <div>Bezel width<i>Sides: 0.78" (19.9mm); top: 0.78" (19.9mm); bottom: 1.12" (28.4mm)</i></div> <div>Dimensions (HxWxD)15.54-19.87" H x 22" W x 10.13" D; 394.8-504.8mm H x 559.6mm W x 257.3mm D</div> <div>Power supply30 watts typical (w/o USB hub), 40 watts maximum (w/o USB hub), &lt;0.5 watts standby/suspend (w/o USB hub), universal, integrated (no external brick-like power supply) 14.70 lb; 6.67kg</div> <div>Weight14.70 lb; 6.67kg</div> <div>Limited warranty<sup>4</sup><b>3 year</b> (includes backlight)</div> <div>Available dateSeptember 2011 / April 2013</div>		<div>Features</div> <div><ul style="list-style-type: none"><li>• Widescreen 24-inch monitor</li><li>• Supports 1920x1200 resolution</li><li>• High Definition (HD) ready; supports 1080p video</li><li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Cable Management for better user experience</li><li>• Carrying handle</li><li>• Recycled content in plastic material</li><li>• Microsoft® Windows® 8 certified</li><li>• PVC/Arsenic/Lead/Mercury free (60A6MAR2US)</li></ul></div>
<div>VESA-compliant<sup>2</sup>VESA DDC2B/CI</div> <div>Power managementENERGY STAR® 5.1 (4420-MB2) ENERGY STAR® 6.0 (60A6MAR2US)</div> <div>ErgonomicsISO 9241-307</div> <div>Emission standardsMPR-2, FCC Class B</div> <div>EnvironmentalTCO Displays 5.2 (4420-MB2), TCO Displays 6.0 (60A6MAR2US), TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b>, ULE Gold</div>	<div></div> <div>ThinkVision LT2452p Wide Monitor</div>	
<div>Preset resolutionsVGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1280x800, 1366x768 WXGA+: 1440x900 UXGA: 1600x1200 WSXGA+: 1680x1050 Full HD: 1920x1080 WUXGA: 1920x1200</div> <div>Presets / user settingsStandard presets: 30; User settings: 20</div>		
<div>Viewing adjustments<i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i></div> <div>Rotating screen<b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller)</div> <div>On screen displayOn screen display with digital user controls (8 languages)</div> <div>Control featuresDirect access (buttons on front) for automatic image setup, input switch, and brightness</div> <div>USB hubUSB 2.0 Hub (1 port into PC, 4 ports for accessories)</div> <div>Multiple inputTriple input (three different PCs attach to three different connectors; one PC shows image; select via button)</div> <div>Monitor connectors(1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, <b>HDCP-compliant</b> (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></div> <div>Signal cables(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</div> <div>Mounting featuresWall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>SecuritySecurity keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>		
<div>Ship groupMonitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter USB cable, 1.8 meter black power cord</div>		

<div>Limited Warranty</div> <div>⇒ <b>3 year limited warranty<sup>4</sup></b></div> <div>⇒ <b>International Warranty Service<sup>5</sup></b></div> <div>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></div> <div>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></div> <div>⇒ <b>Service upgrade options<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (Lenovo Services part number 41C9209)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></div> <div>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></div>	<div>Accessories</div> <div><table><tr><td>DisplayPort to DisplayPort Monitor Cable</td><td>0A36537</td></tr><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr><tr><td>ThinkCentre Extend Arm</td><td>57Y4352</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr></table></div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>	DisplayPort to DisplayPort Monitor Cable	0A36537	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
DisplayPort to DisplayPort Monitor Cable	0A36537												
Kensington MicroSaver Cable Lock	73P2582												
Kensington Twin Head Cable Lock	45K1620												
Lenovo Security Cable Lock	57Y4303												
ThinkCentre Extend Arm	57Y4352												
Lenovo Easy Reach Monitor Stand	55Y9258												

See footnotes for important warranty information  
US model announced September 13, 2011 or April 16, 2013  
US model 4420-MB2 withdrawn effective October 31, 2013

Name	Pro2820 Wide Flat Panel Monitor	Features
Case color	Black	
Type-model	60B5RAR6US	<ul style="list-style-type: none"><li>• 28-inch MVA (Multi-domain Vertical Alignment) panel LED backlit monitor</li><li>• Supports 1920x1080 resolution</li><li>• 5-Ports USB hub, support USB 3.0</li><li>• Arsenic/Mercury free</li><li>• Microsoft® Windows® 7</li><li>• Windows 8/ Windows 8.1 certified</li></ul>
Panel	TFT-LCD, with wide viewing angle (WVA) technology, White LED backlight	
Viewable image size	28" (711mm) diagonal	
Max view area (W x H)	24.44" x 13.44" (620.9mm x 341.3mm)	
Optimum resolution	1920x1080	
Max pixel rate	205MHz (VGA); 165MHz(DP/ HDMI); 149MHz (MHL)	
Frequency	Supports 1920 x 10800 @ 60Hz	
Aspect ratio	16:9	
Pixel pitch (mm)	0.32 x 0.32mm	
Dot/Pixel per Inch	79 dpi	
Brightness	300 nits or cd/m² (typical)	
Contrast ratio	3000:1 (typical)	
Pixel response time	6.5ms	
Color gamut	72%	
Viewing angle at 10:1 CR	178° horizontal, 178° vertical	
Stand	Tilt, swivel, and height adjustable stand	
Bezel width	Sides: 0.86" (21.85mm)	
Dimensions	17.45" H x 26.21" W x 2.30" D;	
(HxWxD, excluding stand)	443.3mm H x 665.9mm W x 58.2mm D	
Dimensions	17.45" H x 26.21" W x 11.41" D;	
(HxWxD, including stand)	443.3mm H x 665.9mm W x 289.9mm D	
Power supply	60 watts typical, 90 watts typical (with USB), 65 watts maximum, 95 watts maximum (with USB), <1.2 watts sleep/off; <0.5 watts switch off integrated (no external brick-like power supply)	
Weight	17.84 lb; 8.11kg (including stand)	
Limited warranty <sup>4</sup>	3 year (includes backlight)	
Available date	September 2014	
VESA-compliant <sup>2</sup>	VESA DDC2B/CI	
Power management	ENERGY STAR® 6.0	
Ergonomics	ISO 9241-307	
Emission standards	FCC Class B	
Environmental	TCO Displays 6.0, TCO Certified Edge 1.2, RoHS, EPEAT™ Gold rating, ULE Gold	
Preset resolutions	VGA: 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1024x760 SXGA: 1280x1024 WXGA: 1280x720, 1280x800, 1366x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080 Others: 1152x864	
Presets / user settings	Standard presets: 17; user settings: 17	
Viewing adjustments	Tilt: 25° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°	
Rotating screen	Screen pivots 90 degrees from landscape to portrait	
On screen display	On screen display with digital user controls (8 languages)	
Control features	Direct access (touch buttons on front) for automatic image setup, input switch, and brightness	
USB hub	USB Hub: one USB 3.0 upstream port, four USB 3.0 downstream ports	
Multimedia	None	
Camera	None	
Multiple input	Support VGA, HDMI, DisplayPort, MHL connections (Mobile High-definition Link)	
Monitor connectors	(1) VGA 15-pin D-shell, analog (2) HDMI (1.4), digital, <b>HDCP-compliant</b> (3) DisplayPort (1.2), digital, <b>HDCP-compliant</b>	
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter	
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group	Monitor, detachable stand, Quick start and safety poster, 1.8 meter DisplayPort cable, 1.8 meter VGA cable, 1.8 meter USB 3.0 cable, 1.8 meter black power cord	
<b>Limited Warranty</b>		
See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a>		
<b>Accessories</b>		
Kensington MicroSaver Cable Lock 73P2582		
Kensington Twin Head Cable Lock 45K1620		
Lenovo Security Cable Lock 57Y4303		
See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>		
See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>		



Name	Pro2840m Wide Flat Panel Monitor	Features
Case color	Black	
Type-model	60B4RAR6US	 <b>ThinkVision Pro2840m Monitor</b>
Panel	TFT-LCD, twisted nematic (TN), White LED backlight	
Viewable image size	28" (711mm) diagonal	
Max view area (W x H)	24.44" x 13.44" (620.9mm x 341.3mm)	
Optimum resolution	3840x2160	
Max pixel rate	300MHz (HDMI); 594MHz(DP); 149MHz (MHL)	
Frequency	Supports 3840 x 2160 @ 60Hz	
Aspect ratio	16:9	
Pixel pitch (mm)	0.16 x 0.16mm	
Dot/Pixel per Inch	157 dpi	
Brightness	270 nits or cd/m² (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	5ms	
Color gamut	72%	
Viewing angle at 10:1 CR	170° horizontal, 160° vertical	
Stand	Tilt, swivel, and height adjustable stand	
Bezel width	Sides: 0.86" (21.85mm)	
Dimensions	17.45" H x 26.21" W x 2.30" D;	
(HxWxD, excluding stand)	443.3mm H x 665.9mm W x 58.2mm D	
Dimensions	17.45" H x 26.21" W x 11.40" D;	
(HxWxD, including stand)	443.3mm H x 665.9mm W x 289.9mm D	
Power supply	60 watts typical, 90 watts typical (with USB), 65 watts maximum, 95 watts maximum (with USB), <1.2 watts sleep/off; <0.5 watts switch off integrated (no external brick-like power supply)	
Weight	22.47 lb; 10.19kg (including stand)	
Limited warranty <sup>4</sup>	3 year (includes backlight)	
Available date	May 2014	
VESA-compliant <sup>2</sup>	VESA DDC2B/CI	
Power management	ENERGY STAR® 6.0	
Ergonomics	ISO 9241-307	
Emission standards	FCC Class B	
Environmental	TCO Displays 6.0, TCO Certified Edge 1.2, RoHS, <b>EPEAT™ Gold rating, ULE Gold</b>	
Preset resolutions	VGA: 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 SXGA: 1280x1024 WXGA: 1280x720, 1280x800, 1360x768 WXGA+: 1440x900, 1600x900 WSXGA+: 1680x1050 Full HD: 1920x1080, 1920x1200 WQXGA: 2560x1600, 2560x1440, other: 3840x2160, 2160x1920	
Presets / user settings	Standard presets: 20; user settings: 20	
Viewing adjustments	Tilt: 25° back, -5° forward; lift: 4.3" (110mm); swivel: +/-45°	
Rotating screen	<b>Screen pivots 90 degrees from landscape to portrait</b>	
On screen display	On screen display with digital user controls (8 languages)	
Control features	Direct access (touch buttons on front) for automatic image setup, input switch, and brightness	
USB hub	USB Hub: 3 USB 3.0, 2 USB 2.0	
Multimedia	Integrated stereo speakers (3 watts x 2)	
Camera	None	
Multiple input	Support HDMI, DisplayPort, mini DisplayPort, MHL connections (Mobile High-definition Link)	
Monitor connectors	(1) HDMI (1.4), digital, <b>HDCP-compliant</b> (2) DisplayPort (1.2), digital, <b>HDCP-compliant</b> (3) mini DisplayPort (1.2), digital, <b>HDCP-compliant</b>	
Signal cables	(1) detachable, HDMI at each end, digital, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter	
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)	
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group	Monitor, detachable stand, Quick start and safety poster, 1.8 meter DisplayPort cable, 1.8 meter HDMI cable, 1.8 meter USB 3.0 cable, 1.8 meter USB 2.0 cable, 1.8 meter black power cord	
Limited Warranty		Accessories
See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a>		Kensington MicroSaver Cable Lock 73P2582
		Kensington Twin Head Cable Lock 45K1620
		Lenovo Security Cable Lock 57Y4303
		See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>
		See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>

Name	ThinkVision 28 Wide Flat Panel Monitor	<b>Features</b> <ul style="list-style-type: none"><li>• 28-inch 4K*2K Tegra K1 entertainment center</li><li>• Supports 3840x2160 resolution</li><li>• 6-Ports USB hub, support USB 3.0 and USB 2.0</li><li>• 5watts x 2 stereo speakers</li><li>• Arsenic/Mercury free</li><li>• 10-point touch screen</li><li>• Windows 7 support</li><li>• Preload android 4.4, 2GB DDR3L memery, 32GB storage</li><li>• Support Gigabit Ethernet, 802.11abgn, Bluetooth 4.0</li></ul>
Case color	Black with Silver bezel	
Type-model	60B6GAR1US	 <p><b>ThinkVision 28 Monitor</b></p>
Panel	TFT-LCD, twisted nematic (TN), White LED backlight	
Viewable image size	28" (711mm) diagonal	
Max view area (W x H)	24.44" x 13.44" (620.9mm x 341.3mm)	
Optimum resolution	3840x2160	
Max pixel rate	297MHz (HDMI); 594MHz(DP)	
Touch	Supports 10-point touch	
Aspect ratio	16:9	
Pixel pitch (mm)	0.16 x 0.16mm	
Dot/Pixel per Inch	157 dpi	
Brightness	300 nits or cd/m <sup>2</sup> (typical)	
Contrast ratio	1000:1 (typical)	
Pixel response time	5ms	
Color gamut	72%	
Viewing angle at 10:1 CR	170° horizontal, 160° vertical	
Stand	Multi-mode stand (standard, inclined, and flat)	
Bezel width	Top: 1.20" (30.5mm) Bottom: 1.98" (50.3mm) Sides: 1.16" (29.5mm)	
Dimensions	16.7" H x 26.85" W x 1.48" D;	
(HxWxD, excluding stand)	424.1mm H x 681.9mm W x 37.6mm D	
Dimensions	19.8" H x 26.85" W x 10.22" D;	
(HxWxD, including stand)	502.8mm H x 681.9mm W x 259.5mm D	
Power supply	55 watts typical, 90 watts maximum, <10 watts sleep/off; <0.5 watts switch off 90W external brick-like power supply	
Weight	24.2 lb; 11.0kg (including stand)	
Limited warranty <sup>4</sup>	1 year (includes backlight)	
Announce date	September 2014	
<b>Smart Mode</b>		
Platform	nVidia Tegra K1 System-on chip	
Preload	Android 4.4 Operating system	
Display RAM	2GB DDR3L memory	
Storage	32GB eMMC storage	
Card slot	One MicroSD Card slot	
Wireless	802.11abgn, Bluetooth 4.0	
Ethernet	Gigabit Ethernet	
Power management	ENERGY STAR® 6.0	
Environmental	TCO Displays 6.0, RoHS, <b>EPEAT™ Gold rating</b>	
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XVGA: 1024x768, 1152x864 SXVGA: 1280x1024, 1280x720, 1280x800, 1280x768 XGA+: 1440x900 UXGA: 1600x900, 1680x1050 WQXGA: 1920x1080, 1920x1200, 2560x1600, QFHD: 3840x2160	
Presets / user settings	Standard presets: 19; user settings: 20	
Viewing adjustments	Tilt: 90° back, -5° forward; lift: 3.07" (78mm);	
Rotating screen	None	
On screen display	On screen display with digital user controls (8 languages)	
Control features	Direct access (touch buttons on front) for automatic image setup, input switch, and brightness	
USB hub	USB Hub: 2 USB 3.0 (one is always on), 2 USB 2.0, 1 micro USB 3.0 upstream, 1 micro USB 2.0 upstream	
Multimedia	Integrated stereo speakers (5 watts x 2), Noise Cancelling array microphone x 2	
Audio Jack	Audio Out Jack x 1 for speakers, Audio In/Out Jack x 1 for headsets	
Camera	FHD camera with 2.1 MP resolution	
Multiple input	Support HDMI, DisplayPort	
Monitor connectors	(1) HDMI (1.4) x 3, digital, <b>HDCP-compliant</b> (2) DisplayPort (1.2) x 1, digital, <b>HDCP-compliant</b>	
Signal cables	(1) detachable, HDMI at each end, digital, 1.8 meter	
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
Ship group	Monitor, detachable stand, Quick start and safety poster, 1.8 meter HDMI cable, 1.8 meter USB 3.0 cable, 1.8 meter external power adapter	
<b>Limited Warranty</b>		<b>Accessories</b>
See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a>		Kensington MicroSaver Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620 Lenovo Security Cable Lock 57Y4303
		See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>
		See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>



Name	<b>T2014 Wide Flat Panel Monitor</b>	<b>Features</b> <ul style="list-style-type: none"><li>• Widescreen 19.5-inch monitor</li><li>• Supports 1600x900 resolution</li><li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li><li>• EPEAT Gold certified</li><li>• Microsoft® Windows® 7 certified</li><li>• Microsoft Windows 8 / Windows 8.1 certified</li></ul>				
Bezel color	<b>Raven black</b>					
Type-model	<b>60C2HAR1US</b>	 <b>ThinkVision T2014 Wide Monitor</b>				
Panel	TFT-LCD, twisted nematic (TN), White LED backlight					
Viewable image size	<b>19.5" (495mm)</b> diagonal					
Max view area (W x H)	17.1" x 9.3" (433.9mm x 236.3mm)					
Native resolution	<b>1600x900</b>					
Aspect ratio	16:9					
Pixel pitch (mm)	0.2712 x 0.2626 mm					
Dot/Pixel per Inch	94.1 dpi					
Brightness	250 nits or cd/m² (typical)					
Contrast ratio	1000:1 (typical)					
Pixel response time	5ms (typical)					
Color gamut	72%					
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical					
Stand	Tilt adjustable stand					
Bezel width	<i>Sides: 0.78" (19.8mm)</i>					
Dimensions (HxWxD)	13.86" H x 18.62" W x 7.47" D; 352.1mm H x 473.0mm W x 189.8mm D					
Power supply	20 watts typical, 22 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)					
Weight	5.56 lb; 2.53 kg					
Limited warranty <sup>4</sup>	<b>3 year</b> (includes backlight)					
Available date	January 2015					
VESA-compliant <sup>2</sup>	VESA DDC2B/CI					
Power management	ENERGY STAR® qualified					
Ergonomics	ISO 9241-307					
Emission standards	FCC Class B					
Environmental	TCO Displays 6.0, TCO Certified Edge 2.0, WEEE, RoHS, <b>EPEAT™ Gold rating</b>					
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900, 1600x900					
Presets / user settings	Standard presets: 24 user settings: 24					
Viewing adjustments	<i>Tilt: 22° backward, -5° forward</i>					
Rotating screen	None					
On screen display	On screen display with digital user controls (8 languages)					
Control features	Direct access (buttons on front) for automatic image setup, dual input and brightness					
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)					
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>					
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter					
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories, 100mm x 100mm mount					
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)					
Ship group	Monitor with stand, Safety and Warranty Information, 1.8 meter analog signal cable, 1.8 meter DVI signal cable, 1.8 meter black power cord					
<b>Limited Warranty</b> See details at <a href="http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281">http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281</a>		<b>Accessories</b> <table><tr><td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr></table> See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>  See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington MicroSaver Cable Lock	73P2582					
Kensington Twin Head Cable Lock	45K1620					

### Disclaimer

Lenovo provides the information in the Product Specifications Reference (PSREF) withdrawn product books on an "AS-IS" basis. Because the actual products have been withdrawn from marketing, the information in these withdrawn product books is no longer maintained or updated. The referenced footnote numbering may not correspond with the listed footnotes.

PSREF books for the withdrawn systems:

[http://www.lenovo.com/psref/psrefs\\_withdrawn.html](http://www.lenovo.com/psref/psrefs_withdrawn.html)

**Availability:** All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

**Warranty:** For a copy of applicable product warranties, go to: [http://support.lenovo.com/en\\_US/product-service/warranty-status/WarrantyPolicies.page](http://support.lenovo.com/en_US/product-service/warranty-status/WarrantyPolicies.page). Lenovo makes no representation or warranty regarding third party products or services.

<sup>1</sup> **ISO-compliant:** Compliance with ISO 9241 Part 3, ISO Part 7, ISO Part 8, and/or ISO 13406 Part 2 is dependent on a complete ISO-capable platform of a system unit, monitor, video subsystem, operating system and fonts.

<sup>2</sup> **VESA:** Requires attachment to suitably configured system with similarly enabled operating system.

<sup>3</sup> **ENERGY STAR:** As an ENERGY STAR partner, Lenovo has determined that this product meets the ENERGY STAR 4.0 or 4.1 guidelines for energy efficiency. Requires attachment to suitably configured system.

<sup>4</sup> **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.

<sup>5</sup> **International Warranty Service** is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.

<sup>6</sup> **Lenovo pays all shipping costs** for warranty repairs during limited warranty period.

<sup>7</sup> **Lenovo Services:** These services are available for machines normally used for business, professional, or trade purposes, rather than personal, family, or household purposes. Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. Service levels are response time objectives and are not guarantees. If the machine problem turns out to be a Customer Replaceable Unit (CRU), a part will be express shipped to you for quick replacement. Onsite 24x7x2-hour service is not available in all locations. P&L means parts and labor. P/U means pick-up. See terms and conditions for complete details and restrictions.

<sup>8</sup> **Telephone support** may be subject to additional charges, even during the limited warranty period. Response times may vary. May exclude some holidays. If a machine is listed as having "On-site service for select repairs", this means that onsite service is available only for the replacement of select parts. For all other warranty repairs, Lenovo will provide the customer a replacement part for customer installation. The parts for which onsite service is available varies by machine, but may include the processor, power supply, heat sink, system board, or base cover. For machines with EasyServ or Courier service, Lenovo will attempt to diagnose and resolve the problem remotely before sending a courier.

<sup>10</sup> **TAA:** Monitor is compliant with the U.S. Federal Government's country-of-origin requirements prescribed in 48 C.F.R. Subpart 25.4; Trade Act Agreement (TAA) model.

<sup>11</sup> **Post-warranty annual maintenance agreement:** Service begins at the end of the base warranty or the end of any other applied warranty and maintenance option, whichever occurs last. Service delivery is not available the same day the maintenance agreement is purchased. Maintenance agreements must be purchased and the registration successfully completed prior to the service being available.

<sup>12</sup> **Halogen:** Less than 900 Parts Per Million. Low halogen is defined in accordance with IPC-401B and draft IPC-J-STD 709 Class 1 requirements.

# ThinkVision®

**Trademarks:** Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, ThinkCentre, ThinkPad, ThinkStation, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Other company, product, or service names may be trademarks or service marks of others.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to alter specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you. This publication was developed in the US.

Visit [www.lenovo.com/safecomputing](http://www.lenovo.com/safecomputing) periodically for the latest information on safe and effective computing.

Visit [www.lenovo.com/psref](http://www.lenovo.com/psref) for the latest version of Product Specifications Reference.

© Lenovo, 2015.  
All rights reserved.

Lenovo  
1009 Think Place  
Morrisville, NC 27560  
U.S.A.

ThinkVision.pdf